



TeleWell®

▶ TW-EA515

TW-EA515 is an ADSL modem which includes enough features to meet the requirements of heavy duty users.

Unit is equipped with fast network interfaces, such as 1 Gbps Switch and 300 Mbps Wlan. It also includes USB port for 3G modems.



- ADSL2+ Modem
- 4 port Ethernet Switch 1Gbps
- Firewall
- Wireless Access Point 802.11n
- Option for 3G Modem



TW-EA515

FEATURES

- Works with any operating system
- IP TV support
- DHCP server
- Support for PPPoE, PPPoA and static IP Address
- Qos
- VPN: PPTP, L2TP (4 incoming/4 outgoing)
- 4 Ethernet ports 1 Gbps
- EWAN function for Wlan router use
- Size: (HxDxW) 36 mm x 148 mm x 210 mm
- Power adapter 15 V DC 1,6 A
- GTIN: 64 3001092 327 5
- Package contains: RJ45 Ethernet cable, RJ11 Phone cable, Filter, 3 Antennas, RS232 cable, Power Adapter and User Guide

ADSL2+

- Supporter modes: Annex A, I, L and M
- Supported ADSL protocols: RFC2684 (previously RFC1483), MPoA, PPPoA, PPPoE
- Max. throughput: Downstream 24 Mbps, Upstream 3,5 Mbps
- Maximum reach: 5-7 km (depending on the variables, i.e. length of the copper pair)

FIREWALL

- NAT/NAPT
- Virtual server and DMZ
- SPI Firewall: Packet and Mac Filter, DOS attack blocking
- Supports DNS relay and dynamic DNS functions
- RIP-1/2 and static routing support
- SNTP support

WIRELESS ACCESS POINT

- Supports 300 Mbps IEEE 802.11b/g/n (DSSS) standard
- Operating frequency: 2,4 GHz
- Automatic data rate fallback 300-1 Mbps
- Automatic channel selection
- WDS
- Operating range up to 300 m (depending on the variables)
- Security: WPA, WPA2, WEP

3G

- USB port for 3G modem
- 3G modem not included